

Thermo Scientific Orion AQUAfast® AQ3010 Turbidity Meter NEW

- Ergonomic IP67 turbidity meter for lab or field use
- Uses Nephelometric principle with 90° detection
- In many locations a separate light cap or shield is not needed
- Meets ISO 7027 and offers consistent light source for greater accuracy
- Easy vial indexing with continuous measurement mode
- No mixing or diluting with polymer bead primary standards for faster calibration
- Three year warranty

The new AQUAfast AQ3010 Turbidity Meter makes it easy to determine the clarity of your sample with one keystroke and without an extra light shield cap in many environments. With autoranging from 0 – 1000 NTUs, this small waterproof portable meter is very easy to use, plus features a large easy-to-read LCD display. The meter is supplied with ready-to-use, highly stable EPA-approved polymer bead primary standards. Calibration is easy with step-by-step prompts with the option to choose which points to calibrate. The standards can be used for a calibration check at any time, verifying that your readings are accurate.

The AQUAfast AQ3010 meter comes with everything you need in a field case for easy storage and transport. This meter is covered by a 3 year warranty!



AQ3010 Meter Kit

Specifications	Description
Display	LCD
Keys	Power, Cal, Scroll Up, Scroll Down, Read/Enter
Automatic Range Selections and Resolution	0.01 to 19.99 NTU with 0.01 NTU resolution
	20.0 to 99.9 NTU with 0.1 NTU resolution
	100-1000 NTU with 1 NTU resolution
Precision	+/- 2% of reading +/- 1 LSD for 0-500 NTU
	+/- 3% of reading +/- 1 LSD for 501-1000 NTU
Response Time	< 6 seconds
Sample Requirement	10 mL
Included Calibration Standards	0.02, 20.0, 100, and 800 NTU
Sample Vials	25 mm diameter with indexing mark
Light Source	IR LED for ISO 7027 Turbidity measurement
Power	4 x AAA > 3000 tests (4 x AAA Lithium > 12000 tests)
Battery conservation feature	Auto shutoff after 20 minutes of inactivity
Ambient Operating Temperature	0 to 50 C (0 to 90% Non-Condensing Relative Humidity at 30 C)
Self Diagnostics	Yes, with troubleshooting error codes
Waterproof rating	IP67
Regulatory Approvals	CE, TUV 3-in-1 for CSA-US, FCC part 15
Warranty	3 year

Ordering Information

Cat. No.	Description	Contents
AQ3010	AQUAfast turbidity meter kit	Meter, set of EPA-approved polymer-based primary turbidity standards, batteries, light shield cover, seven vials, lint-free cloth, silicone oil, MSDS and user guide
AC301S	Replacement set of EPA-approved polymer-based primary turbidity standards	60 mL bottle of 0.02, 20.0, 100, and 800 NTU
AC3SIL	Replacement silicone oil and cloth	1 bottle of silicone oil and one cloth
AC3V25	Replacement 25 mm vials, pack of 3	3 empty 25 mm vials with caps
AC3CBR	Replacement vial cleaning brush	Brush, package of 10

Make your job easier!

Visit our new applications webpage at <http://www.thermo.com/waterapps> for regulatory links, methods, applications and technical information.